




ACAD GENERATED DRAWING. DON'T CHANGE BY HAND


PITCH 0.5mm FPC CONNECTOR SMT TYPE



PCB Layout



REV	DATE	ECN NO.	MODIFICATION	APPROVER
B	2010/12/15	RD00310121501	版本升级	HYQ
C	2012/04/13	RD00312021301	重新整理图面	Jason_Lee
D	2018/04/17	RD00318041703	夹持盖加长为12mm, 改为26pin以上pin位用	Jason_Lee



SPECIFICATION

1.Material:

Housing: Thermoplastic, UL94V-0,color:Natural .
Lock: Thermoplastic, UL94V-0,color:black.
Contacts: Copper alloy,
Tin/Gold plated over nickel plated (50 u" min)
Solder tab: Copper alloy,
Tin/Gold plated over nickel plated (50 u" min)
Cover: Thermoplastic, UL94V-0,color:Natural.

2.Electrical Characteristics:

Voltage rating: 50V(max).
Current rating : 0.5A(max).
Operating Temperature: -25°C~+85°C.
Insulation resistance: 500M ohms min. at 500VDC
Dielectric withstanding voltage: 250 VAC/1minute.
Contact resistance: 20m ohms max.

NOTES:

"▲"Dimension:
4Pin~29Pin: 4.60mm;
30Pin~45Pin: 4.80mm;
46Pin~60Pin: 5.20mm;

"■"Dimension:
4Pin~29Pin: 1.40mm;
30Pin~45Pin: 1.60mm;
46Pin~60Pin: 2.00mm;

PIN NO.	A	B	C	D
26	12.50	13.60	17.30	18.65
27	13.00	14.10	17.80	19.15
28	13.50	14.60	18.30	19.65
29	14.00	15.10	18.80	20.15
30	14.50	15.60	19.30	20.65
31	15.00	16.10	19.80	21.15
32	15.50	16.60	20.30	21.65
33	16.00	17.10	20.80	22.15
34	16.50	17.60	21.30	22.65
35	17.00	18.10	21.80	23.15
36	17.50	18.60	22.30	23.65
37	18.00	19.10	22.80	24.15
38	18.50	19.60	23.30	24.65
39	19.00	20.10	23.80	25.15
40	19.50	20.60	24.30	25.65
41	20.00	21.10	24.80	26.15
42	20.50	21.60	25.30	26.65
43	21.00	22.10	25.80	27.15
44	21.50	22.60	26.30	27.65
45	22.00	23.10	26.80	28.15
46	22.50	23.60	27.30	28.65
47	23.00	24.10	27.80	29.15
48	23.50	24.60	28.30	29.65
49	24.00	25.10	28.80	30.15
50	24.50	25.60	29.30	30.65
51	25.00	26.10	29.80	31.15
52	25.50	26.60	30.30	31.65
53	26.00	27.10	30.80	32.15
54	26.50	27.60	31.30	32.65
55	27.00	28.10	31.80	33.15
56	27.50	28.60	32.30	33.65
57	28.00	29.10	32.80	34.15
58	28.50	29.60	33.30	34.65
59	29.00	30.10	33.80	35.15
60	29.50	30.60	34.30	35.65

GENERAL TOLERANCE				UNITS	NAME:	ATOM® 深圳市爱特姆科技有限公司 SHENZHEN ATOM TECHNOLOGY CO., LTD.		
SELECT	TOL	1	2	3	mm	0.5mm FPC Connector	TITLE:	
DN.	1	2	3		MAT'L	PART NO:	0.5mm FPC 立贴式(反脚)全包 (H=2.0mm)	
X.XXX	±0.10	±0.05	±0.15		FINISH	APPD: Jason_Lee	DWG NO. ATOM-A01498	
X.XX	±0.15	±0.10	±0.25		Q'TY	CHKD: Vicky	SCALE	SHEET
X.X	±0.20	±0.25	±0.5			DR: Aimee		
X.	±0.30	±0.36	±1.00				1:1	1/1
ANGLE	±2°						REV	D