






5	6	7	8
REV.	DATE	ECN NO.	MODIFICATION
A	2016/07/07	/	NEW
			APPROVER
			Jason



0.08MAX




P.C.B LAYOUT
REFERENCE TOLERANCE: ±0.05

SPECIFICATIONS:

- 1.Current Rating:SIGNAL PIN 0.3A/PIN,POWER PIN 5A/PIN
- 2.Insulation Resistance: 1000Megohms min
- 3.Dielectric Withstanding : AC 500V
- 4.Operating Temperature : -40°C~+85°C

Electrical Characteristics:

- 1.Contact Mateed rial: Copper Alloy
 - 2.Insulator Material: Thermoplastic,UL94V-0
 - 3.plating: Gold plated
- Lead free and ROHS compliant product

GENERAL TOLERANCE				UNITS mm	NAME: BTB		ATOM [®] 深圳市爱特姆科技有限公司 SHENZHEN ATOM TECHNOLOGY CO., LTD.				
SELECT TOL. ON.	✓	1	2		3	MAT'L	PART NO: BTB080006-F1S15200	TITLE: Customer Drawing For BTB0.8mm 6P 母座 合高H=0.6mm 卷装			
X.XXX	±0.10	±0.05	±0.15		FINISH		APPD: Jason	DWG NO. ATOM-A04105		SCALE	SHEET
X.XX	±0.15	±0.13	±0.25			CHKD: DAVID	1:1			1/1	A
X.X	±0.20	±0.25	±0.50		Q'TY	DR: HUJING					
X.	±0.30	±0.38	±1.00								
ANGLE	±2°										

5

6

7

8