







1 2 3 4 5 6 7 8


REV.	DATE	ECN NO.	MODIFICATION
A0	2023.01.06	/	NEW
A1	2024.08.28	RD00324082801	配合试纸厚度改0.30mm加胶



3D VIEW



Section:A-A



DEFAULT TOLERANCE:±0.05

NOTES:

Material:

- A.Housing:LCP UL94V-0,Color-Black
- B.Terminal:C5210 T=0.15±0.01mm
- C.Slider:LCP UL94V-0,Color-Black

2.Plation of Contact

Contact Area AU 5U"MIN
Soldering Area G/F

Electrical :

- 1.Rating current: 0.3A
- 2.Insulation resistance:100MΩ MIN at 500V DC
- 3.Contact Resistance 50mΩ MAX
- 4.Withstanding Voltage: 500V AC for 1 minute

Mechanical:

- 1.Insertion force:2N MAX
- 2.Withdrawal force:0.2N MIN
- 3.Mating Cycles : 50000Cycles

Environment characteristics:

- 1.Operating: - 20°C to +70°C
- Nonoperating: - 25°C to +85°C

MAJOR DIMENSION:▼

GENERAL TOLERANCE			UNITS mm	NAME(INTENDED USE) 3+5 8Pin 反向试条插座	PART NO.(INTENDED USE) GP20A-06200	TITLE: 3+5 8Pin 反向试条插座 H=3.0mm
SELECT	1	2				
TOL. ON:	1	2	3			
X.XXX	±0.10	±0.15	±0.20			
X.XX	±0.15	±0.20	±0.25			
X.X	±0.20	±0.25	±0.30			
X.	±0.25	±0.30	±0.50			
ANGLE	±2°					
MAT'L			FINISH	APPD:	CHKD:	DWG NO.: ATOM-A07904
Q'TY			DR: ming20240826	SCALE 1:1	SHEET 1/1	REV. A1

1 2 3 4 5 6 7 8